

1. **Introduction**

2. **Background**

3. **Methodology**

4. **Results**

5. **Discussion**

6. **Conclusion**

7. **References**

8. **Appendix**

9. **Index**

10. **Table of Contents**

2

3

4

5

6

7

8

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

- 1 wherein said sheet material has a longitudinal area extending
2 between said first plurality of orifices, and second plurality of
3 orifices in-line, for fabricating said toroidal sleeve.
- 4 3. The device as defined in claim 2, wherein said toroidal sleeve is
5 fabricated by stitching a first longitudinal edge of said
6 longitudinal area and a second longitudinal edge of said
7 longitudinal area, together.
- 8 4. The device as defined in claim 3, wherein said toroidal sleeve has
9 a foam flotation element housed therein.
- 10 5. The device as defined in claim 4, wherein said sheet material is
11 flexible plastic material.
- 12 6. The device as defined in claim 1, wherein said circular bottom
13 component is fabricated out of sheet material having at least one
14 orifice therein for permitting chum matter to pass through.
- 15 7. The device as defined in claim 6, wherein said circular bottom
16 component is permanently attached by stitching near a circumference
17 thereof and near said lower edge of said cylindrical containing
18 component.
- 19
- 20 8. The device as defined in claim 7, wherein a welting has edges sewn
21 in between said circumference of said circular bottom component and
22 said lower edge of said cylindrical containing component.
- 23 9. The device as defined in claim 8, wherein said sheet material is
24 flexible plastic material.

- 10027358-12601
- 1 10. A method of fabricating a device for holding a bucket of chum
2 submerged in water comprising the steps of:
3 a) forming a circular bottom component;
4 b) forming a rectangular sheet of material having a first
5 plurality of orifices therein for permitting chum matter to
6 pass through;
7 c) forming an upper edge mechanism on said rectangular sheet of
8 material for cooperating with a drawstring;
9 d) forming a sleeve by stitching together, a first longitudinal
10 edge and a second longitudinal, edge of a longitudinal area of
11 said rectangular sheet of material, for housing a foam
12 flotation element;
13 e) forming a cylindrical containing component by stitching two
14 side edges of said rectangular sheet of material together;
15 f) attaching a circumference of said circular bottom component to
16 a lower edge of said cylindrical containing component;
17 g) inserting said foam flotation element into said sleeve;
18 h) threading said drawstring through said upper edge mechanism.
- 19 11. The method of fabricating a device as defined in claim 10, further
20 comprising the additional step of; attaching edges of a welting in
21 between said circumference of said circular bottom component and
22 said lower edge of said cylindrical containing component